



# HX1302/HX1402

The New Standard in Agricultural Tractors

## COMFORT to work SOLUTION



Heated premium seat



Auto folding auxiliary seat



Tilting and telescopic steering



Electronic armrest



Air conditioner



Option  
Hot and cold storage box with wireless mobile phone charging

## CONVENIENCE to work SOLUTION



Full LED Headlight



LED front work lights / rear work lights



Wide transparent sunroof



Rear wiper & Hot wire



4WD switch



USB charging + power socket

Seamless comfort, optimal efficiency.

# HX1302/HX1402

## PERFORMANCE to work SOLUTION

**3.8ℓ diesel engine independently developed by KIOTI**

HX1402	
140 Max. Power Hp/2,200 rpm	540 Max. Torque Nm/1,400 rpm
HX1302	
130 Max. Power Hp/2,200 rpm	530 Max. Torque Nm/1,400 rpm

### Convenient maintenance

With its easy-to-open one-piece hood structure, maintenance tasks such as oil filter and air cleaner filter replacement, oil filling, oil gauge checking, coolant inspection, as well as cleaning are convenient.



4,410 kg-f lifting force



Option

Added weight  
Front: 50kg×10ea(500kg), 50kg×14ea(700)  
Rear : 100kg×2ea(200kg)



230ℓ capacity fuel tank



Front axle LSD



32-speed transmission  
(8 speeds x 2 ranges x 2 speeds)



Power shift  
(8 speeds)

## LINK to work SOLUTION



Electronic rear 3-point hitch



14 hydraulic ports  
(2 are optional)



One-hand quick coupler



PTO



Remote rear fender PTO &  
3pt switch (Left / Right)



Turn-up / back-up

## SPECIFICATIONS

MODEL		HX1302	HX1402
ENGINE		4JTA-TP5A	
Engine gross	Hp(kw)	130.1 (97.0)	140.1 (104.5)
Fuel tank	(ℓ)	230	
<b>TRANSMISSION</b>			
Type		Power shift Transmission	
Speed		32Fx32R with Multi wet disc clutch	
PTO type & speed		Independent (3 speed) with Ground PTO	
Auto 4WD brake		STD.	
Differential		Front: LSD, Rear: Mechanical differential lock	
<b>HYDRAULIC SYSTEM</b>			
3 Point lift control type		Electronic control with remote switch at rear, Quick Cat.2	
Hydraulic flow	(lpm)	Total 121 (1st: 74.8 / 2nd: 46.2)	
Lift capacity		4,410kg @lift point (Max.), 3,630kg @610mm point	
External valve		F6 / R6	
<b>DIMENSION</b>			
Wheel base	(mm)	2,600	
Overall LEN. (w/o front weight and w/3pt hitch)	(mm)	4,518	
Overall height (CAB)	(mm)	2,906	
<b>TIRE SIZE</b>			
Front AG.		420 / 70R28	
Rear AG.		520 / 70R38	

\*NOTE: Specifications and design are subject to change without notice.

### STANDARD EQUIPMENT

- Auto 4WD
- Auto PTO
- PTO cruise
- Speedmeter
- Escort lamp control
- External hydraulic cylinder
- Joystick valve
- Front & Rear fender
- Telescopic & Dual rear view mirror
- Air conditioner / heater
- Rear window wiper
- Air suspension & Heated seat
- External 3-point lift control (button)
- Ground PTO
- 7 pin socket
- Tilting & Telescopic steering
- Instruction Seat
- Backward Alarm
- One touch floating

### OPTIONAL EQUIPMENT

- Front & Rear weight
- Hydraulic valve (Detent floating / Three detent floating)
- Hot and cold storage box with wireless mobile phone charging
- Beacon
- Side working lamp
- Top Link Cylinder
- Free flow Kit



ISO 9001  
NO.954596



ISO 14001  
NO.771475



OHSAS 18001  
NO:K033008



**Daedong Kioti Europe B.V.**  
World Trade Center Rotterdam  
Beursplein 37, 3011 AA Rotterdam, The Netherlands  
Tel +31(0)85 10 63 580  
Website www.kioti.eu



צ.ל.ע. ציוד לעבודות עפר בע"מ  
גשר העץ 46, פארק תעשיות עמק חפר  
טלפון 04-6225591  
אתר www.cla.co.il



**צ.ל.ע. ציוד לעבודות עפר בע"מ**  
Earth Moving Equipment Ltd.