



HX1302/HX1402

The New Standard in Agricultural Tractors

COMFORT to work SOLUTION



Heated premium seat

Auto folding auxiliary seat

Tilting and telescopic steering



Electronic armrest

Air conditioner

Option
Hot and cold storage box with wireless mobile phone charging

CONVENIENCE to work SOLUTION



Full LED Headlight

LED front work lights / rear work lights

Wide transparent sunroof



Rear wiper & Hot wire

4WD switch

USB charging + power socket

Seamless comfort, optimal efficiency.

HX1302/HX1402

PERFORMANCE to work SOLUTION

3.8ℓ diesel engine independently developed by KIOTI

HX1402	
140 Max. Power Hp/2,200 rpm	540 Max. Torque Nm/1,400 rpm
HX1302	
130 Max. Power Hp/2,200 rpm	530 Max. Torque Nm/1,400 rpm

Convenient maintenance

With its easy-to-open one-piece hood structure, maintenance tasks such as oil filter and air cleaner filter replacement, oil filling, oil gauge checking, coolant inspection, as well as cleaning are convenient.



4,410 kg-f lifting force



230ℓ capacity fuel tank



Electronic rear 3-point hitch



Front axle LSD




32-speed transmission
(8 speeds x 2 ranges x 2 speeds)



Power shift
(8 speeds)



14 hydraulic ports
(2 are optional)



One-hand quick coupler



PTO



Remote rear fender PTO &
3pt switch (Left / Right)



Turn-up / back-up

LINK to work SOLUTION



SPECIFICATIONS

MODEL	HX1302	HX1402
ENGINE	4JTA5	
Engine gross	Hp(kw)	130.1 (97.0)
Fuel tank	(ℓ)	230
TRANSMISSION	Power shift Transmission	
Type	32FX32R with Multi wet disc clutch	
Speed	Independent (3 speed) with Ground PTO	
PTO type & speed	STD.	
Auto 4WD brake	Front: LSD, Rear: Mechanical differential lock	
Differential	Front: LSD, Rear: Mechanical differential lock	
HYDRAULIC SYSTEM	Electronic control with remote switch at rear, Quick Cat.2	
3 Point lift control type	Total 121 (1 st : 74.8 / 2 nd : 46.2)	
Hydraulic flow	(lpm)	4,410kg @lift point (Max.), 3,630kg @610mm point
Lift capacity	F6 / R6	
External valve	F6 / R6	
DIMENSION	7915	
Wheel base	(mm)	2,600
Overall LEN. (w/o front weight and w/3pt hitch)	(mm)	4,518
Overall height (CAB)	(mm)	2,906
max permissible weight	7915	
TIRE SIZE	420 / 70R28	
Front AG.	520 / 70R38	
Rear AG.		

*NOTE : Specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Auto 4WD
- Auto PTO
- PTO cruise
- Speedmeter
- Escort lamp control
- External hydraulic cylinder
- Joystick valve
- Front & Rear fender
- Telescopic & Dual rear view mirror
- Air conditioner / heater
- Rear window wiper
- Air suspension & Heated seat
- External 3-point lift control (button)
- Ground PTO
- 7 pin socket
- Tilting & Telescopic steering
- Instruction Seat
- Backward Alarm
- One touch floating

OPTIONAL EQUIPMENT

- Front & Rear weight
- Hydraulic valve (Detent floating / Three detent floating)
- Hot and cold storage box with wireless mobile phone charging
- Beacon
- Side working lamp
- Top Link Cylinder
- Free flow Kit



ISO 9001
NO.954596



ISO 14001
NO.771475



OHSAS 18001
NO:K033008



Daedong Kioti Europe B.V.
World Trade Center Rotterdam
Beursplein 37, 3011 AA Rotterdam, The Netherlands
Tel +31(0)85 10 63 580
Website www.kioti.eu



צ.ל.ע ציוד לעבודות עפר בע"מ
גשר העץ 46, פארק תעשיות עמק חפר
טלפון 04-6225591
אתר www.cla.co.il

